

Operator's Manual SRM-2620U Grass Trimmer / Brushcutter

WARNING

The engine exhaust from this product contains chemicals known to the State of California to cause cancer, birth defects, or other reproductive harm.

A WARNING



Read and understand all provided literature before use. Failure to do so could result in serious injury.

Note: This product complies with CAN ICES-2/NMB-2.

TABLE OF CONTENTS

| Introduction | |
|--|------|
| Servicing Information | |
| Parts and Serial Number | 4 |
| Service | 4 |
| ECHO Consumer Product Support | 4 |
| Product Registration | 4 |
| Additional Literature | |
| Safety | |
| Manual Safety Symbols and Important Information | 5 |
| International Symbols | 6 |
| International SymbolsPersonal Condition and Safety Equipment | 0 |
| Equipment | 0 |
| Emission Control | . 10 |
| Emission Control | . 13 |
| CARB and EPA Emission Control Information | . 15 |
| Description | . 16 |
| | |
| Installation | |
| U-handle Installation | |
| Throttle Linkage and Ignition Lead Installation | . 19 |
| Blade Installation | . 20 |
| Debris Shield Installation | . 22 |
| Nylon Line Head Installation | . 23 |
| Advance Trimmer Line | . 23 |
| Balance and Adjust Unit | . 24 |
| Operation | |
| Operation with Blades | 25 |
| Blade Selection | 27 |
| Fuel | |
| Starting Cold Engine | |
| Starting Warm Engine | 33 |
| Stopping Engine | |
| Applications | . 34 |
| Applications | . 33 |
| Operating Techniques - Nylon Line Head | . აა |
| Operating Techniques - Metal or Plastic Blade | . 36 |
| Reaction Forces | . 37 |
| Blade Cutting Problems | |
| Maintenance | |
| Skill Levels | . 40 |
| Maintenance Intervals | |
| Air Filter | |
| Fuel Filter | |
| Spark Plug | . 44 |
| Cooling System | . 44 |
| Exhaust System | . 45 |
| Carburetor Adjustment | . 47 |
| Lubrication | 48 |
| Nylon Line Head Disassembly Instructions | 40 |
| Nylon Line Replacement | 40 |
| Sharpening Metal Blades | 50 |
| Troubleshooting | 50 |
| Storage | . JZ |
| Specifications | . J4 |
| Draduat Dagistration | . 54 |
| Product Registration | . ၁6 |

INTRODUCTION

Specifications, descriptions, and illustrative material in this literature are as accurate as possible. Specifications are subject to change without notice. Illustrations might include optional equipment and accessories, and might not include all standard equipment. Your equipment might appear slightly different than pictured equipment.



Read and understand all provided literature. Literature contains specifications and information for safety, operation, maintenance, storage, and assembly specific to this product. Scan QR codes for more information.



For additional literature, including safety manuals where applicable, or questions regarding terms used in this manual, visit:

https://www.echo-usa.com/manuals



OR


https://www.shindaiwa-usa.com/manuals



SERVICING INFORMATION

Parts and Serial Number

Genuine ECHO parts and assemblies for your ECHO products are available only from an Authorized Service Dealer, When vou do need to buy parts, always have the model number and serial number of the unit with you. Image shows serial number location. For future reference write them in the space provided below.



| Model No. | Serial No. |
|-----------|------------|
| | |

Service

Service of this product during the warranty period must be performed by an Authorized Service Dealer. For the name and address of the Authorized Service Dealer nearest you, ask your retailer or call 1-800-432-ECHO (3246). Authorized Service Dealer information is also available on our website www.echo-usa.com. When presenting your unit for warranty service/repairs, proof of purchase is required.

ECHO Consumer Product Support

If you require assistance or have questions concerning the application, operation, or maintenance of this product, call the ECHO Consumer Product Support Department at 1-800-432-ECHO (3246) from 8:00 a.m. to 5:00 p.m. (Central Standard Time) Monday through Friday. Before calling, please know the model and serial number of your unit.

Product Registration

Register your ECHO equipment online at www.echo-usa.com or by filling out the product registration sheet included in this manual. Registering your product confirms warranty coverage and provides a direct link to ECHO if we find it necessary to contact you.

Additional Literature

In addition to finding information online, information is available from your Authorized Service Dealer, or by contacting ECHO Incorporated, 400 Oakwood Road, Lake Zurich, IL 60047, 1-800-432-ECHO (3246).

SRM-2620U SAFETY

SAFETY

Manual Safety Symbols and Important Information

Throughout this manual and on the product itself, you will find safety alerts and helpful, informational messages preceded by symbols or key words. The following is an explanation of those symbols and key words and what they mean to you.

DANGER

The safety alert symbol accompanied by the word "DANGER" calls attention to an act or condition which WILL lead to serious personal injury or death if not avoided.

WARNING

The safety alert symbol accompanied by the word "WARNING" calls attention to an act or condition which COULD lead to serious personal injury or death if not avoided.

CAUTION

The safety alert symbol accompanied by the word "CAUTION" calls attention to an act or condition which might lead to minor or moderate personal injury if not avoided.

The enclosed message provides information necessary for the protection of the unit.

Note: This enclosed message provides tips for use, care and maintenance of the unit.



CIRCLE AND SLASH SYMBOL

This symbol means the specific action shown is prohibited. Ignoring these prohibitions can result in serious or fatal injury. **SAFETY**

International Symbols

| Symbol | Description | Symbol | Description |
|-------------|---|-------------------|--|
| | Warning, see operator's manual. | H | Carburetor adjustment (high speed) |
| | Wear eye, ear and head protection. | T | Carburetor adjustment (idle speed) |
| | Wear hand and foot protection. | L | Carburetor adjustment (low speed) |
| \triangle | Safety/Alert | STOP | STOP switch |
| | Hot surface | + | Fuel and oil mixture |
| | Do not allow flames or sparks near fuel. | Ignition ON OFF O | lgnition ON / OFF |
| 3 | Do not smoke near fuel. | • | Purge bulb |
| + | Choke control RUN position (choke open). | 1 | Choke control COLD START position (choke closed). |
| | Keep feet away from blade. | | Rotating cutting attachment. |

| Symbol | Description | Symbol | Description | |
|-------------|---|---|---|--|
| | Thrown objects | | Direction of blade | |
| | Do not use line heads, use blades only. | | Do not use blades, use line heads only. | |
| S A Ham(SO) | | Keep bystande 15 m (50 ft.). | rs and helpers away | |
| | | Avoid kick-out. Keep bystanders and helpers away 15 m (50 ft.). | | |
| | | Beware of thrown objects. Wear eye protection. | | |

Note: Not all symbols will appear on your unit.

X7532340502



7

SAFETY SRM-2620U

Personal Condition and Safety Equipment

WARNING

Cancer and Reproductive Harm www.P65Warnings.ca.gov

WARNING

The muffler or catalytic muffler and surrounding cover may become extremely hot. If unit is equipped with muffler, always keep clear of exhaust and muffler area, otherwise serious personal injury might occur.

WARNING

Users of this product risk injury to themselves and others if the unit is used improperly and/or safety precautions are not followed. Proper clothing and safety gear must be worn when operating unit.

Physical Condition

Your judgment and physical dexterity may not be good:

- · If you are tired or sick
- · If you are taking medication
- If you have taken alcohol or drugs

Operate unit only if you are physically and mentally well.

Eye Protection

WARNING

- · Eye protection that meets ANSI Z87.1 or CE requirements must be worn whenever you operate the unit.
- · For additional safety, a full-face shield (not included) can be worn over safety glasses or goggles to provide protection from sharp branches or flying debris.



SRM-2620U SAFETY

Hand Protection

Wear sturdy, no-slip, rubber work gloves to improve your grip on the handles. Gloves also provide protection against cuts and scratches, cold environments, and reduce the transmission of machine vibration to your hands.

Hearing and Ear Protection

ECHO recommends wearing personal protective equipment whenever unit is used.

Breathing Protection

Operators who are sensitive to dust or other common airborne allergens may need to wear a dust mask to prevent inhaling these materials while operating unit. Dust masks can provide protection against dust, plant debris, and other plant matter such as pollen. Make sure the mask does not impair your vision, and replace the mask as needed to prevent air restrictions.

Proper Clothing

Wear snug-fitting, durable clothing:

- Pants should have long legs, shirts should have long sleeves.
- · Do not wear shorts.
- · Do not wear ties, scarves, jewelry, or clothing with loose or hanging items that could become entangled in moving parts or surrounding growth.
- Keep clothing buttoned or zipped, and keep shirt tails tucked in.
- Wear sturdy work shoes with nonskid rubber soles.
- Do not wear open toed shoes.
- Do not operate unit with bare feet.
- · Keep long hair away from engine and air intake. Retain hair with cap or net.

Heavy protective clothing can increase operator fatigue, which may lead to heat stroke. Schedule heavy work for early morning or late afternoon hours when temperatures are cooler.

SAFETY

WARNING

The components of this machine generate an electromagnetic field during operation, which can interfere with some pacemakers. To reduce the risk of serious or fatal injury. persons with pacemakers should consult with their physician and the pacemaker manufacturer before operating this machine. In the absence of such information, ECHO does not recommend the use of this machine by anyone who has a pacemaker.

Extended Operation and Extreme Conditions

CAUTION

Prolonged exposure to cold and/or vibration can result in injury. Read and follow all safety and operation instructions to minimize risk of injury. Failure to follow instructions can result in painful wrist/hand/arm injuries.

It is believed that a condition called Raynaud's Phenomenon, which affects the fingers of certain individuals, may be brought about by exposure to vibration and cold. Exposure to vibration and cold may cause tingling and burning sensations, followed by loss of color and numbness in the fingers. The following precautions are strongly recommended, because the minimum exposure which might trigger the ailment is unknown.

- Keep your body warm, especially the head, neck, feet, ankles, hands, and wrists.
- Maintain good blood circulation by performing vigorous arm exercises during frequent work breaks, and also by not smoking.
- Limit the hours of operation. Try to fill each day with jobs where operating the unit or other hand-held power equipment is not required.
- If you experience discomfort, redness, and swelling of the fingers followed by whitening and loss of feeling, consult your physician before further exposing yourself to cold and vibration.



SRM-2620U SAFETY

Repetitive Stress Injuries (RSI)

It is believed that overusing the muscles and tendons of the fingers, hands, arms, and shoulders may cause soreness, swelling, numbness, weakness, and extreme pain in those areas. Certain repetitive hand activities may put you at a high risk for developing a Repetitive Stress Injury (RSI). An extreme RSI condition is Carpal Tunnel Syndrome (CTS), which could occur when your wrist swells and squeezes a vital nerve that runs through the area. Some believe that prolonged exposure to vibration may contribute to CTS. CTS can cause severe pain for months or even years.

To reduce the risk of RSI/CTS, do the following

- Avoid using your wrist in a bent, extended, or twisted position. Instead try to maintain a straight wrist position. Also, when grasping, use your whole hand, not just the thumb and index finger.
- Take periodic breaks to minimize repetition and rest your hands.
- Reduce the speed and force with which you do the repetitive movement.



- Do exercises to strengthen the hand and arm muscles.
- Immediately stop using all power equipment and consult a doctor if you
 feel tingling, numbness, or pain in the fingers, hands, wrists, or arms. The
 sooner RSI/CTS is diagnosed, the more likely permanent nerve and
 muscle damage can be prevented.

DANGER

All over head electrical conductors and communications wires can have electricity flow with high voltages. This unit is not insulated against electrical current. Never touch wires directly or indirectly, otherwise serious injury or death can result.

▲ DANGER

Do not operate gas-powered products indoors or in inadequately ventilated areas. Engine exhaust contains poisonous emissions and can cause serious injury or death.

SAFETY SRM-2620U

Read Manuals

 Provide all users of this equipment with literature for instructions on safe operation.

Clear the Work Area

- · Always clear the work area of foreign objects such as rocks, broken glass, nails, wire, or string, and check for any hidden hazards. Spectators and fellow workers must be warned, and children and animals prevented from coming nearer than 15 m (50 ft.) while the unit is in use.
- Outside the 15 m (50 ft.) zone, there is still a risk of injury from thrown objects.
- Bystanders should be encouraged to wear eye protection.
- If you are approached, stop the engine and cutting attachment.
- When a bladed unit is used, there is the added risk of injury to bystanders being struck with the moving blade in the event of a blade thrust or other unexpected reaction of the blade.

Keep a Firm Grip

· Always hold throttle handle and support handle with thumbs and fingers tightly encircling the handles.

Keep a Solid Stance

- · Maintain footing and balance at all times. Do not stand on slippery, uneven or unstable surfaces. Do not work in odd positions or on ladders. Do not overreach
- Keep cutting attachment below waist.
- Keep all body parts away from rotating cutting attachment.

Avoid Hot Surfaces

 If unit is equipped with muffler, keep exhaust area clear of flammable debris. Avoid contact during and immediately after operation.





SRM-2620U SAFETY

Equipment

WARNING

Use only approved attachments. Serious injury may result from the use of a non-approved attachment combination. ECHO Incorporated will not be responsible for the failure of cutting devices, attachments or accessories which have not been tested and approved by ECHO Incorporated. Read and comply with all safety instructions.

- · Do not attempt to modify this product. Serious injury can result from the use of any modified product.
- · Check unit for loose or missing nuts, bolts, and screws. Tighten or replace as needed.
- · Inspect shield for damage and ensure that shield is properly installed, and that the cut-off knife is securely in place. Replace if either is damaged or missing.
- · Check that the cutting attachment is firmly attached and in safe operating condition.
- · Ensure that manufacturer recommended flexible nonmetallic line is installed in the trimmer head.
- · Ensure that throttle trigger, throttle trigger lockout, and stop switch all work properly.
- · Check that handle and harness (if included) are installed and adjusted for safe, comfortable operation. See Assembly Section for proper adjustment.

WARNING

Moving parts can amputate fingers or cause severe injuries. Keep hands, clothing and loose objects away from all openings.

- · Always stop engine, disconnect spark plug, and make sure all moving parts have come to a complete stop before assembling unit, removing obstructions, clearing debris, or servicing unit.
- · Do not connect spark plug lead to spark plug until unit is ready for use.
- · Do not start or operate unit unless all guards and protective covers are properly assembled to unit.
- · Never reach into any opening while the engine is running. Moving parts may not be visible through openings.

SAFETY SRM-2620U

· Position wiring safely to prevent snagging, separation of connectors, or breakage during operation. Gather excess wire, and secure with wiring clamp if provided on equipment, or tuck behind the air filter area. Do not place wiring directly against hot engine components.

- · Check wiring and connectors for nicks, cuts, exposed wire, or other damage, and repair or replace as needed. Exposed wire or connectors can cause shocks, sparks, and risk of fire or explosion, resulting in serious injury.
- · Check wire terminals for secure connections.

WARNING

Periodically check fuel system (fuel lines, vent, grommet, fuel tank, and fuel cap) for leaks especially if the unit is dropped. If damage or leaks are found, do not use unit, otherwise serious personal injury or property damage may occur. Have unit repaired by an Authorized Service Dealer before using.



EMISSION CONTROL

CARB and EPA Emission Control Information

The emission control system for the engine is EM (engine modification) and, if the second to last character of the Engine Family on the Emission Control Information label (sample below) is "B", "C", "K", or "T", the emission control system is EM and TWC (3-way catalyst). The fuel tank/fuel

EMISSION CONTROL INFORMATION ENGINE FAMILY: (2) EHXS.0214EQ DISPLACEMENT: 21.2cc EMISSION COMPLIANCE PERIOD: SOHours THIS ENGINE MEETS 2013 U.S.EPA EXH/EVP & CALIFORNIA EXH/EVP EMISSION REGULATIONS FOR S.O.R.E. REFER TO OWNER'S MANUAL FOR MAINTENANCE SPECIFICATIONS AND ADJUSTMENTS.

YAMABIKO CORP. MMM/YYYY



line emission control system is EVAP (evaporative emissions). Evaporative emissions for California models are only applicable to fuel tanks and fuel feed lines

An Emission Control Label is located on the engine. (This is an EXAMPLE ONLY, information on label varies by engine FAMILY).

EMISSION CONTROL INFORMATION

ENGINE FAMILY: CEHXS.0214KL DISPLACEMENT: 21.2cc EMISSION COMPLIANCE PERIOD: 300Hours THIS ENGINE MEETS 2012 U.S. EPA EXHVEVP & CALIFORNIA EXH/EVP EMISSION REGULATIONS FOR S.O.R.E. REFER TO OWNER'S MANUAL FOR MAINTENANCE SPECIFICATIONS AND ADJUSTMENTS.

YAMABIKO CORP. MMM/YYYY [E]




Product Emission Durability (Emission Compliance Period)

The 50 or 300 hour emission compliance period is the time span selected by the manufacturer certifying the engine emissions output meets applicable emissions regulations, provided that approved maintenance procedures are followed as listed in the Maintenance Section of this manual.

DESCRIPTION

Locate the safety decal(s) or etching(s) on your unit. Make sure they are legible, and that you understand and follow the instructions. If any cannot be read, replacements can be ordered from your Authorized Service Dealer. Images shown below are for example only. Those on your unit might appear slightly different.



- 1. Spark plug
- 2. Top guard
- 3. Spark arrester muffler or spark arrester muffler with catalyst
- 4. Fuel tank
- 5. Fuel tank cap
- 6. Air filter
- 7. Choke
- 8. Purge bulb
- 9. Recoil starter handle
- 10. Power head
- 11. Stop switch
- 12. Throttle trigger lockout
- 13. Throttle trigger
- 14. Harness hanger
- 15. U-handle
- 16. I ower drive shaft
- 17. Debris shield with cut-off knife
- 18. Cut-off knife
- 19. Speed-Feed® 400 head
- 20. Debris shield without cut-off knife
- 21. Shoulder harness
- 22. Hip pad

CONTENTS SRM-2620U

CONTENTS

The ECHO product you purchased has been factory pre-assembled for your convenience. Due to packaging restrictions, some assembly may be necessary.

After opening the carton, check for damage. Immediately notify your retailer or ECHO Dealer of damaged or missing parts. Use the contents list to check for missing parts.

- 1 Power head / drive shaft assembly
- U-handle assembly 1
- 1 Operator's manual
- 1 Warranty statement
- Shield without cut-off knife
- 1 U-handle mounting clamp (lower)
- 1 U-handle mounting clamp (upper)
- 1 U-handle bolt
- Flat washer 1
- 2 Cable clips
- 3 Lock nuts (shield mount)
- 1 Lower blade fixing plate
- 1 Large nut (blade mounting)
- 1 Shoulder harness with hip pad
- 2 Cotter pins




INSTALLATION


U-handle Installation

Parts required: U-handle, U-handle clamps, U-handle bolt, flat washer.

- Place U-handle (A) between Uhandle clamps (B).
- 2. Assemble flat washer (C) and U-handle bolt (D) to U-handle clamps (B) and semi-tighten.
- Place U-handle assembly on 3. driveshaft bracket (E).
- 4. Tighten U-handle bolt (F).




5. Route throttle linkage and ignition lead assembly (G) along driveshaft and clip as shown




Throttle Linkage and Ignition Lead Installation

- 1. Close choke and remove air filter cover and air filter.
- 2. Insert throttle wire assembly into adjustment fixture and install wire end (A) into large carburetor throttle swivel hole.
- Turn throttle wire retaining clip clockwise to lock into place.
- Check throttle for freedom of movement. Verify wide open throttle and low idle are adjusted properly.



Note: The throttle linkage must be adjusted by moving the adjustment nut. Consult with your Authorized Service Dealer for correct adjustment procedure.

- 5. Connect ignition stop leads (D) from throttle cable assembly to ignition leads (E) on engine.
- Assemble air filter. 6.
- 7 Assemble air filter cover.



Blade Installation

WARNING

You must install the U-handle and all blade conversion parts shown in the following instructions before operating this unit with a metal blade, otherwise serious injury may result.

WARNING


Shield with cut-off knife is for use with the nylon line head only. Install shield without cut-off knife when using plastic or metal blades, or serious injury may result.

Note: Blades must be selected for type of cutting being performed.

Shield without Cut-off Knife Installation


Parts required: Shield without cut-off knife, shield plate, three bolts, three lock nuts.

- 1. If installed, remove nylon line head, line head plate, shield plate, and shield with cut-off knife.
- 2. Align notch in edge of shield and hole in line head plate with notch in edge of gear housing.
- 3. Insert head locking tool (A) into line head plate.
- 4. Turn line head (B) clockwise to remove it.
- 5. Remove locking tool (A).



X7532340502


- 6. Remove line head plate.
- 7. Remove three bolts holding shield plate and shield with cut-off knife to gear housing.
- 8. Retain line head, shield plate, and shield with cut-off knife for future use.
- 9. Align holes in shield plate (D), shield (E), to holes in bottom of gear case flange.
- 10. Install and tighten bolts (F) and lock nuts (G).



Blade Installation

Parts required: Upper plate with pilot, lower plate, 10 mm nut with left-hand threads, 2 x 25 mm cotter pin, blade.

- Install upper plate with pilot (A) 1. on splined PTO shaft, pilot side out.
- Match blade (B) on upper plate 2. pilot (A) so rotation arrow on blade matches rotation of indicated on the blade shield.
- 3. Secure blade with lower plate (C), and 10 mm left-hand threaded nut (D). Turn nut counterclockwise on PTO shaft to tighten.
- Align hole in upper plate with notch in gear housing, and insert locking tool (E) to prevent splined shaft from turning.



Never reuse a cotter pin. Install a new cotter pin each time a blade is installed or replaced.

- 5. Insert cotter pin (F) in hole in PTO shaft, and bend pin legs around shaft counterclockwise to retain the 10 mm nut.
- 6. Remove locking tool (E).


Debris Shield Installation

Parts required: Shield with cut-off knife, shield plate, three bolts, nylon line head, plate.

WARNING

Shield with cut-off knife is for use with the nylon line head only. Install shield without cut-off knife when using plastic or metal blades, or serious injury may result.

- Remove blade mounting hardware, blade, and shield without cut-off 1. knife, and retain for future use.
- 2. Align holes in shield (A) and shield plate (B) to bottom of gear case flange.
- 3. Install and tighten bolts (C).
- 4. Place line head plate (D) on PTO shaft (E).



Nylon Line Head Installation

Parts required: Nylon line head.

A CAUTION


Wear gloves or personal injury may result:

- · Cut-off knife is sharp.
- · Gear case and surrounding area may be hot.

Semi-automatic nylon line heads must be used only with debris shield with cut-off knife. Using nylon line heads with debris shield without cut-off knife can result in trimmer damage, caused by operation with excessive line length.

Note: Your nylon line head may appear different than nylon line head shown.

- Align notch in edge of shield 1. and hole in line head plate with notch in edge of gear housing and insert head locking tool (A).
- Thread line head (B) onto PTO 2. shaft by turning it counterclockwise until head is tight against line head plate.
- Remove locking tool (A). 3.




Advance Trimmer Line


Tap trimmer head against ground while nylon line head is turning at normal operating speed.

OPERATION SRM-2620U

Balance and Adjust Unit

- 1. Loosen harness clamp screw (A).
- Put on harness and attach to 2. unit
- Slide harness clamp (B) back 3. and forth along driveshaft until unit balances with cutting head approximately 50-75 mm (2-3 in.) from the ground.
- Tighten harness clamp screw (A).
- Loosen U-handle clamp screws 5. (C), and position U-handle for comfortable operation.





OPERATION

WARNING

Moving parts can amputate fingers or cause severe injuries. Keep hands, clothing and loose objects away from all openings. Always stop engine, disconnect spark plug, and make sure all moving parts have come to a complete stop before removing obstructions, clearing debris, or servicing unit.

WARNING

Engine exhaust is hot, and contains Carbon Monoxide (CO), a poison gas. Breathing CO can cause unconsciousness, serious injury, or death. Exhaust can cause serious burns. Always position unit so that exhaust is directed away from your face and body.



WARNING

Operation of this equipment may create sparks that can start fires around dry vegetation. This unit is equipped with a spark arrester to prevent discharge of hot particles from the engine. Metal cutters can also create sparks if the cutter strikes rocks, metal, or other hard objects. Contact local fire authorities for laws or regulations regarding fire prevention requirements.

Operation with Blades

WARNING

Metal blades are very sharp and can cause severe injuries, even if unit is off and blades are not moving. Avoid contact with blades. Wear gloves to protect hands.

WARNING

Blade use demands specific brushcutter configuration. Operation without specified shield, barrier bar or U-handle, and harness can result in serious personal injury. Follow installation instructions.

| | AL TO BE UT | GRASS | WEED/ GRASS | WEED/ GRASS | BRUSH <12.7 MM (0.5 in.) | CLEARING <63.5 MM (2.5 in.) |
|------------------------|--|--|--|---|--------------------------------|-------------------------------------|
| Cutting Attachm | Cutting Nylon line head | | Maxi-Cut head / Pro Maxi-Cut Head | 3-tooth blade / 8-tooth blade | 80- tooth blade | 22-tooth blade |
| You must install | You must Shield included DSRM, DPAS to attachm models Cut Hear for CT- | | nts, or GT PRO Maxi- is not rated | Brushcutter shield supplied with U and C model brushcutters, blade conversion kit or PAS and DPAS brushcutter attachments | | |
| these parts | Handle | Standard handle included with SRM, DSRM, T, PAS and DPAS or GT models (PRO Maxi-Cut Head is not rated for GT models) | | U-Handle* or support handle with barrier bar supplied with U and C model brushcutters, blade conversion kit or PAS and DPAS brushcutter attachments | | vith U and C blade S and DPAS |

OPERATION SRM-2620U

| | AL TO BE UT | GRASS | WEED/ GRASS | WEED/ GRASS <12.7 MM <63.5 M | | CLEARING <63.5 MM (2.5 in.) |
|-----------------------------------|--|-----------------|---|--|--------------|-----------------------------------|
| | Harness | Not requir | red** | | ushcutters a | with U and C and blade |
| You must | Upper/ lower plate adapter and washer | Not required | Washer required, included with cutting attachment | Upper/lower blade plate adapte included with U and C model brushcutters, blade conversion kit or PAS and DPAS brushcutte attachments | | C modeİ conversion |
| install these parts Hex nut | | Not required | Hex nut required, included with cutting attachment | | | utters, blade and DPAS |
| | Cotter pin | Not required | New cotter pin included with cutting attachment | New cotter pin included with U and C model brushcutters, blade conversion kit or PAS and DPAS brushcutter attachments | | utters, blade and DPAS |

^{*}ANSI standards require brushcutters be equipped with a support handle with barrier bar or restrictive harness.

WARNING

Do not install blades on GT (curved shaft) model trimmers.

- Use only ECHO approved parts. Failure to use the correct parts can cause the blade to fly off. Serious injury to the operator and/or bystanders can occur.
- Arbor diameter of upper blade plate must match arbor diameter of blades.
- For barrier bar or U-handle, follow instructions supplied with either blade conversion kit or U-handle kit, and verify blade is secured properly.
- · A new cotter pin is required each time a blade is installed.
- · Shoulder harnesses may be used on all trimmers and brushcutters to reduce operator fatigue. Brushcutters over 7.5 kg (16.5 lb.) and U-handle brushcutters require a double shoulder harness.



^{**} Grass trimmers do not require a harness if dry weight is below 6.0 kg (13.2 lb). For grass trimmers having a dry weight of 6.0 kg (13.2 lb) to 7.5 kg (16.5 lb), a single-shoulder harness is required. A harness may be used as outlined in this Operator's Manual.

^{***} Brushcutters require a single shoulder harness, at a minimum, if the dry weight is below 7.5 kg (16.5 lb).

SRM-2620U OPERATION

Note: The barrier bar is used to restrict rearward movement of the unit. The barrier bar is not a handle and should not be gripped when using or carrying the unit.

Blade Selection

WARNING

An improper or dull blade can cause serious personal injury. The type of blade used must be matched to the type and size of material cut. Blades must be sharp. Dull blades increase the chance of kick-out and injury to yourself and bystanders. Never use an edging blade, circular saw blade, or any other type of unapproved blade.

Not all blades are compatible with all trimmers. Visit www.echousa.com or www.shindaiwa-usa.com to find compatible blades.

3-Tooth Grass/Weed Blade may be used wherever the nylon line head is used. DO NOT use this blade for heavy weeds or brush.

8-Tooth Weed/Grass Blade is designed for grass, garden debris and thick weeds up to 19 mm (0.75 in.) diameter. Do not use this blade for brush or heavy woody growth.

80-Tooth Brush Blade is designed for cutting brush and woody growth up to 13 mm (0.5 in.) diameter.

22-Tooth Clearing Blade is designed for dense thickets and saplings up to 64 mm (2.5 in.) diameter.


WARNING

A trimmer/brushcutter with a metal blade can cause serious injuries if handled improperly.

OPERATION SRM-2620U

Use care when carrying or handling the equipment to avoid contact with the cutting edges of the blade. Use the optional blade cover when unit is not in use.

Keep blades in protective packaging until ready to install. Store blades safely after removal to prevent injury from accidental contact.




Use blade protectors to protect blade teeth during unit transportation.

Use Shoulder/Waist Harness

ECHO recommends using a shoulder/waist harness for all trimmer / brushcutter use, not just blade operation. The harness suspends the trimmer from the operator's shoulder and reduces operator fatique.

The harness also increases operator safety by reducing the possibility of blade contact with the operator's hands and feet by restricting trimmer movement.



Ensure sure the warning sign on the back of the shoulder harness can be read easily.

Note: In case of emergency, disconnect the trimmer from the harness.

Fuel

WARNING

Diesel fuels and alternative fuels, such as E15 (15% ethanol), E85 (85% ethanol) or any fuels not meeting ECHO requirements are not approved for use in ECHO two-stroke or hybrid fourstroke gasoline engines. Use of diesel or alternative fuels may cause performance problems, loss of power, overheating, fuel vapor lock, and unintended machine operation, including, but not limited to, improper clutch engagement. Diesel or alternative fuels may also cause premature deterioration of fuel lines, gaskets, carburetors and other engine components.



Fuel Requirements

Gasoline - Use fresh (purchased within the last 30 days from the pump) 89 Octane [R+M/2] (mid grade or higher) gasoline known to be good quality. Gasoline may contain up to 10% Ethanol (grain alcohol) or 15% MTBE (methyl tertiary-butyl ether). Gasoline containing methanol (wood alcohol) is not approved. Use of ECHO branded fuel is recommended to extend engine life in all air-cooled two-stroke and two or four-stroke hybrid engines.

Two-Stroke Oil - A two-stroke engine oil, such as ECHO branded twostroke oils, meeting ISO-L-EGD (ISO/CD 13738) and J.A.S.O. FD Standards must be used. ECHO branded two-stroke oils meet these standards. Engine problems due to inadequate lubrication caused by failure to use an ISO-L-EGD (ISO/CD 13738) and J.A.S.O. M345-FD certified oil will void the two-stroke engine warranty.

WARNING

Two-stroke engine oil contains petroleum distillates and other additives that may be harmful if swallowed. Heated oil can release vapors that can cause flash fire, or ignite with explosive force. Read and follow the oil manufacturer's instructions, and observe all safety warnings and precautions for handling flammable liquids. For more detailed safety and first aid information, visit www.echo-usa.com for a copy of the Material Safety Data Sheet.

- · Keep out of reach of children.
- If swallowed, do not induce vomiting. Call physician or a poison control center immediately.
- · Wear safety glasses when mixing or handling.
- Avoid repeated or prolonged skin contact.
- · Avoid inhaling oil mists or vapors.

ECHO branded two-stroke oils may be mixed at 50:1 ratio for application in all ECHO engines sold in the past, regardless of ratio specified in those manuals.

Handling Fuel

Fuel is flammable. Use extreme care when mixing, storing or handling, or serious personal injury may result.

- · Use an approved fuel container.
- Do not smoke near fuel.
- · Do not allow flames or sparks near fuel.
- · Fuel tanks/cans may be under pressure. Always loosen fuel caps slowly allowing pressure to equalize.
- · Never refuel a unit when the engine is hot or running.
- · Do not fill fuel tanks indoors. Always fill fuel tanks outdoors over bare ground.
- · Do not overfill fuel tank. Wipe up spills immediately.
- · Securely tighten fuel tank cap and close fuel container after refueling.
- · Inspect for fuel leakage. If fuel leakage is found, do not start or operate unit until leakage is repaired.
- · Use caution when handling fuel. Mix and pour fuel outdoors where there are no sparks and flames. Slowly remove the fuel cap only after stopping the engine and allowing the unit to cool. Do not smoke while fueling or mixing fuel. Move the unit at least 3 m (10 ft.) from the fueling point before starting the engine.

Gasoline vapor is heavier than air, and can travel along the ground to nearby sources of ignition such as electrical motors, pilot lights, and hot or running engines. Vapors ignited by an ignition source can flash back to the fuel container, resulting in an explosion, fire, serious or fatal injuries, and extensive property damage.

Mixing Instructions

- Fill an approved fuel container with half of the required amount of gasoline.
- Add the proper amount of engine oil to gasoline.
- 3. Close container and shake to mix oil with gasoline.
- Add remaining gasoline, close fuel container, and remix.

| Fuel to Oil Mix – 50:1 Ratio | | | | | |
|------------------------------|---------|--------|-----|--|--|
| U | S | Metric | | | |
| Gas | Oil | Gas | Oil | | |
| gal. | fl. oz. | L | СС | | |
| 1 | 2.6 | 5 | 100 | | |
| 2 | 5.2 | 10 | 200 | | |
| 5 | 13 | 25 | 500 | | |

NOTICE

Spilled fuel is a leading cause of hydrocarbon emissions. Some states may require the use of automatic fuel shut-off containers to reduce fuel spillage.

After use

· Empty the fuel tank prior to storing the unit. Return unused fuel to an approved fuel storage container.

Storage - Fuel storage laws vary by locality. Contact your local government for the laws affecting your area. As a precaution, store fuel in an approved, airtight container. Store in a well-ventilated, unoccupied building, away from sparks and flames.

NOTICE

Stored fuel ages. Do not mix more fuel than you expect to use in thirty days or ninety days when a fuel stabilizer is added.

Stored two-stroke fuel may separate. Always shake fuel container thoroughly before each use.


Used oil and gasoline, and soiled towels are hazardous waste materials. Disposal laws vary by locality.

Starting Cold Engine


WARNING

The attachment will operate immediately when the engine starts, and could result in possible serious injury. Keep movable parts of the attachment away from objects that could become entangled or thrown, and surfaces that could cause loss of control.

Move stop switch button (A) forward, away from the STOP position.




- Move choke lever (B) to COLD 2. START position.
- Pump purge bulb (C) until fuel 3. is visible and flows freely in the clear fuel tank return line. Pump bulb an additional four or five times.



NOTICE

Lightly place knee on drive shaft to stabilize unit during starting. Do not apply excessive downward force or damage to unit can occur.

Lav the unit on a flat surface and keep movable attachment parts clear of all obstacles. Firmly grasp throttle handle and throttle trigger lockout with left hand and fully depress throttle trigger to wide open position. Rapidly pull recoil starter handle/rope (D) until engine starts (or maximum five pulls).



5. After engine fires (or five pulls), move choke lever back to RUN position. Firmly grasp throttle handle and throttle trigger lockout with left hand and fully depress throttle trigger to wide open position. Pull recoil starter handle/rope until engine starts and runs. Release throttle trigger, and allow unit to warm up at idle for several minutes.

Note: If engine does not start with choke in RUN position after five pulls, repeat instructions 2 - 5.

After engine warm-up, grip throttle handle and support handle. Depress the throttle trigger lockout, and gradually depress throttle trigger to increase engine RPM to operating speed.

Starting Warm Engine


The starting procedure is the same as Cold Start except do not close the choke, and do not hold throttle trigger fully depressed.

WARNING


The attachment should not move at idle, otherwise serious personal injury may result.

Note: If attachment moves, readjust carburetor according to Carburetor Adjustment instructions in this manual or see your dealer.

Move stop switch button (A) forward away from the STOP position.



Pump purge bulb (C) until fuel is visible in the clear fuel return line.




NOTICE

Lightly place knee on drive shaft to stabilize unit during starting. Do not apply excessive downward force or damage to unit can occur.

Lay the unit on a flat surface and keep movable attachment parts clear of all obstacles. Firmly grip throttle handle and throttle trigger lockout with left hand. Rapidly pull recoil starter handle/rope (D) until engine starts.


> Note: If engine does not start after five pulls, use Cold Start Procedure.



Stopping Engine

Release throttle trigger and allow engine to return to idle before shutting off engine.

> Move stop switch button (A) backward to STOP position.



WARNING

If engine does not stop when stop switch is moved to STOP position, close choke - COLD START position - to stall engine. Have your dealer repair stop switch before using unit again.

Applications

WARNING

Incorrect unit positioning can cause loss of control and serious personal injury. Always hold throttle handle with right hand and support handle with left hand, positioning unit on right side of body.

WARNING

Do not install blades on GT (Curved Shaft) or T model trimmers.

Operating Techniques - Nylon Line Head

Nylon line heads may be used for trimming, scything, edging, and scalping of grass and light weeds.

Units with Speed-Feed® line heads only: To advance trimmer line, tap trimmer head against the ground while the head is turning at normal operating speed.

Trimming

Feed the spinning line into the material to be cut. Tilt the line head to one side to direct cutting debris away from you:

- Model SRM/PAS/SB/TX/C/T (Straight shaft, counterclockwise line **head rotation):** Tilt the cutting head down on the right side (muffler side) while cutting to direct cutting debris away from operator. Feed the line gradually into the material you wish to cut, avoiding contact with fences or other barriers.
- GT models: Tilt cutting head to the left while cutting to direct debris away from the operator.

Scything

Scything - Swing the cutting head in a level arc, gradually feeding the line into the material being cut. Move forward with each arc to cut a swath. Width of cutting swath depends on arc. Use a larger arc for a wider swath, or a smaller arc for a narrow swath. Keep line head tilted to direct cutting debris forward or away from you.

OPERATION SRM-2620U

Edging and Scalping

Both of these are done with the nylon line cutting head tilted at a steep angle. Scalping is removing top growth, leaving the earth bare. Edging is trimming the grass back where it has spread over a pavement or driveway. During both edging and scalping, hold the unit at a steep angle in a position where the debris, and any dislodged dirt and stone, will not come back towards you even if it ricochets off the hard surface.

General

- Debris flows in direction of line head rotation. Change line head position to ensure debris flow is directed away from operator.
- Keep cutting line away from wire fences to avoid entanglement.
- · Operate trimmer only with cutting head below knee height.

Operating Techniques - Metal or Plastic Blade

Brush cutter blades may be used to cut and trim a wide variety of materials, refer to the blade selection section for determining the correct blade for the application.

Scything (3-, 8-, and 80-tooth weed/grass, and brush blades)

 To cut large sections of field grass and weeds swing the cutting head in a level arc, gradually feeding the blade into the material being cut. Adjust throttle speed according to the work.

 Do not swing the main pipe with arms. Turn hips to swing the blade horizontally from right to left, and cut weeds on the left side of the blade.

- Do not scythe back and forth as the grass may scatter and kickback may occur easily.
- Tilt blade left by 5 to 10 degrees so that cut grasses will push left, making progress easier.
- · Move forward with each arc to cut a swath.
- Width of cutting swath depends on arc. Use a larger arc for a wider swath, or a smaller arc for a narrow swath. Suggested cutting width is about 1.5 m (4.9 ft).
- When scything large brush up to 0.5 in. diameter from right to left, avoid cutting with highlighted section.



SRM-2620U OPERATION

Reaction Forces

WARNING

- · The cutting attachment will continue to rotate even after the throttle is released, maintain control of the unit until it has come to a complete stop.
- · Blade thrust may occur when the spinning blade contacts an object that it does not immediately cut. Following proper cutting techniques will prevent blade thrust.
- · Blade thrust can be violent enough to cause the unit and/or operator to be propelled in any direction, and possibly lose control of the unit.
- Blade thrust can occur without warning if the blade snags, stalls or binds.
- · Blade thrust is more likely to occur in areas where it is difficult to see the material being cut.

Push or Pull - Kickout

During normal use, operating a brushcutter with a circular metal blade can produce sudden strong reaction forces that are difficult to control. Strong reaction forces can cause a loss of balance or loss of control of the equipment, resulting in serious injury to operator and bystanders.

Understanding what causes these reactive forces may help you to avoid them, and can help you to maintain control of the equipment if you experience a sudden reaction during cutting. Reactive forces occur when the force being applied by the cutting teeth of a blade meet resistance, and some of the cutting force is directed back toward the equipment. The greater the cutting force or the amount of resistance, the greater the reactive force.

OPERATION SRM-2620U

Push and Pull Forces


Push and pull forces are reactive forces that push the equipment directly toward the operator, or that pull the equipment directly away from the operator. These forces are the result of cutting on the sides of the blade. The direction of the force depends on the side of the blade being used, and the direction of blade rotation at the point of contact. The reactive force is in the opposite direction of blade rotation at the contact point, regardless of where the contact is being made. These types of reactive forces are also called "blade thrust."As shown in the illustration, a blade turning counterclockwise will cause the equipment to pull away from the operator if the point of cutting resistance is on the left side of the blade. If the point of cutting resistance is on the right side of the blade, the equipment will push back toward the



operator. In both examples, the reactive force is in the opposite direction of blade rotation at the contact point where resistance occurs.

Kickout

Kickout is also a reactive force caused by resistance to cutting, but the direction of blade thrust is lateral (to the left or right of the blade), instead of forward or back toward the operator. In most cases, push, pull, and kickout can be reduced or eliminated by:




- Using properly sharpened blades.
- · Applying consistent, even force to the blade during the cut.
- Avoiding obstacles and ground hazards.
- · Using extra care when cutting harder materials such as extremely dry brush, saplings, and small trees.
- Cutting from a stable, secure position.

Blade Cutting Problems

Binding - Blades may bind in the cut if dull or forced. Binding can damage blade, and result in blade breakage or injury from fragments and flying debris. If a blade binds in a cut, do not try to get it out by applying up and down force to pry the cut open. Applying prying force to the blade can bend the blade, and result in blade failure and injury.





To free a blade that is bound in the cut, stop the engine, and support the trimmer or brushcutter to keep stress off the blade. Push the tree away from the entry point of the cut to open the cut, and pull the blade directly away from the cut in a straight-line motion. Use caution when releasing the tree to avoid being struck by spring-back or falling.

Inspect the blade for damage before proceeding. Sharpen teeth if dull, or replace blade if cracked, bent, missing teeth, or otherwise damaged.

To prevent binding:

- Keep blades sharp.
- Avoid excessive pressure during cuts.
- · Do not exceed cutting capacity of blade.
- Do not use blades with damaged or missing cutting teeth.
- · Do not tilt blade when cutting.

MAINTENANCE

WARNING

Moving parts can amputate fingers or cause severe injuries. Keep hands, clothing and loose objects away from all openings. Always stop unit, disconnect spark plug or remove battery, and make sure all moving parts have come to a complete stop before removing obstructions, clearing debris, or servicing unit. Allow the unit to cool before performing maintenance or adjustments. Wear gloves to protect hands from sharp edges and hot surfaces

WARNING

Operating a poorly maintained unit can result in serious injuries to operator or bystanders. Always follow all maintenance instructions as written, otherwise serious personal injury can result.

Your unit is designed to provide of trouble-free service. Perform regular scheduled maintenance. If you are unsure about the task, or are not equipped with the necessary tools, we recommend that you take your unit to an Authorized Service Dealer for maintenance. To help you decide whether you want to do it yourself or have the Authorized Service Dealer do it, each maintenance task has been graded. If a task is not listed, see your Authorized Service Dealer for repairs.

NOTICE

The use of emission control components other than those specifically designed for this unit is a violation of federal law.

Skill Levels

Level 1 = Easy to do. Common tools may be required.

Level 2 = Moderate difficulty. Some specialized tools may be required.

Level 3 = See your Authorized Service Dealer.

Click HERE or go to http://www.echo-usa.com/products/maintenance-kit or

https://www.shindaiwa-usa.com/you-can.aspx

Maintenance Intervals

| COMPONENT / SYSTEM | MAINTENANCE PROCEDURE | SKILL LEVEL |
|-----------------------|-------------------------------|----------------|
| Daily or Before Use | | |
| Air filter | Inspect / Clean * | |
| Choke shutter | - Inspect / Olean | 1 |
| Fuel system | Inspect ¹ | |
| Cooling system | Inspect / Clean | 2 |
| Recoil starter rope | Inspect / Clean * | 1 |
| Screws / nuts / bolts | Inspect / Tighten / Replace * | • |
| Blade | Inspect / Replace * | 1 |
| Every Refuel | | |
| Fuel system | Inspect ¹ | 1 |
| 3 Months | | |
| Air filter | Replace * | |
| Fuel filter | Inspect * | 1 |
| Fuel cap gasket | Порсог | |

| COMPONENT / SYSTEM | MAINTENANCE PROCEDURE | SKILL LEVEL |
|------------------------------------|--|----------------|
| Spark plug | Inspect / Clean / Replace * | 1 |
| Muffler spark arrester | mapeot / Olean / Replace | |
| Cylinder exhaust port | Inspect / Clean / Remove carbon deposits | 2 |
| Drive shaft (flex cable models) | Grease ² | 2 |
| Gear housing (certain models) | Grease ³ | |
| Yearly | | |
| Fuel filter | Inspect / Replace * | 1 |
| Fuel cap gasket | Replace* | • |

Note: Time intervals shown are maximum. Actual use and your experience will determine the frequency of required maintenance.

^{*} Replacement is recommended based on the finding of damage or wear during inspection.

¹ Low evaporative fuel tanks do not require regular maintenance to maintain emission integrity.

² Apply lithium-based grease every 25 hours of use.

³ Apply lithium-based grease every 50 hours of use.


Air Filter

Level 1


Parts required: Tune-up kit.

- Close choke (COLD START position). This prevents dirt from entering the carburetor throat when the air filter is removed.
- 2. Brush accumulated dirt from air cleaner area.


Ensure throttle wire retaining clip (A) remains in place as shown when removing or installing air filter cover.



3. Remove air filter cover (B). Clean inside and out.



- 4. Remove foam filter (C).
- 5. Remove foam filter cage (D).
- 6. Clean foam filter (C) in water/ detergent solution and rinse with clean water.
- 7. Wrap foam filter (C) in a clean, dry cloth and squeeze (do not wring) dry. Dry completely before reuse. Do not oil.
- Remove air filter (E). 8.



- 9. Brush debris from air filter (E). Replace if damaged, fuel soaked, very dirty, or the rubber sealing edges are deformed.
- 10. Assemble air filter (E).
- Assemble foam filter cage.(D).
- 12. Assemble foam filter (C).
- 13. Assemble air filter cover (B).

Fuel Filter

Level 1

Parts required: Tune-up kit.

WARNING

Fuel is flammable. Mixing, transporting, or storing fuel, could result in fire. Do not allow flame or spark near fuel. Use care when handling.

- Use a clean cloth to remove loose dirt from around fuel tank cap. 1.
- 2. Remove fuel tank cap.
- 3. Empty fuel into an approved container.

Do not damage fuel line while removing fuel filter from tank.

- 4. Remove fuel filter (A) from fuel tank and inspect it.
- 5. Replace if dirty or damaged.
- Leave wire coil clamp in place. 6. Pinch fuel filter with fingers on one hand and hold fuel line with other hand. Pull and twist slightly to separate.
- 7. Install new fuel filter with reverse action.
- 8. Rinse inside of fuel tank with gasoline if dirty.

Note: Federal EPA regulations require all model year 2012 and later gasoline powered engines produced for sale in the United States to be equipped with a special low permeation fuel supply hose between the carburetor and fuel tank. When servicing model year 2012 and later equipment, only fuel supply hoses certified by EPA can be used to replace the original equipment supply hose. Fines up to \$37,500 may be enforced for using a replacement part that is not certified.

Spark Plug


Level 2

Parts required: Tune-up kit.

NOTICE

Use only NGK CMR7H spark plug. Do not sand blast to clean or severe engine damage can occur.

- 1. Remove spark plug from cylinder.
- 2. Place piston at top dead center (TDC).
- 3. Check spark plug for fouling, worn, or rounded center electrode.
- Clean park plug or replace with 4. a new one.
- 5. Set spark plug gap to 0.65 mm (0.026 in.).
- Tighten spark plug to 102-153 6. kgf•cm (89-133 lbf•in).



Cooling System

Level 2

NOTICE

To maintain proper engine operating temperatures, cooling air must pass freely through engine covers and reach cylinder fin area. This flow of air carries combustion heat away from the engine.


Overheating and engine seizure can occur when:

- · Engine covers are blocked, preventing cooling air from reaching the cvlinder fin area.
- Dust and grass build up on outside of the cylinder and cylinder fin area. This build up insulates the engine and prevents cooling.

Removal of cooling passage blockages or cleaning of outside of cylinder and cylinder fin area is considered normal maintenance. Failure due to lack of maintenance is not covered by warranty.

Cooling System Cleaning


- 1. Remove muffler cover (A).
- 2. Remove engine cover (B).



NOTICE

Use brush with nylon bristles to remove dirt from cylinder fins. Do not use a metal brush or metal scraper.

- 3. Remove air filter cover.
- Brush debris from grid (C) between recoil starter and fuel tank.
- Assemble engine cover (B). 5.
- 6. Assemble muffler cover (C).




Exhaust System

Level 2

Spark Arrester Screen Cleaning

Parts required: Spark arrester screen, gasket.

- 1. Remove muffler cover (A).
- 2. Remove spark arrester screen cover (B), gasket (C), and spark arrester screen (D), from muffler body.



NOTICE


When cleaning carbon deposits, do not damage catalytic element inside muffler.

- 3. Clean carbon deposits from muffler components.
- 4. Replace spark arrester screen if it is cracked, plugged, or has holes burned through.
- 5. Assemble spark arrester screen (D), gasket (C), and spark arrester screen cover (B), to muffler body.
- 6. Assemble muffler cover.

Exhaust Port Cleaning

Parts required: Heat shield (as needed).


- Remove muffler cover.
- 2. Remove muffler (A).
- 3. Remove heat shield (B).



NOTICE

Use a wood or plastic scraping tool to clean deposits from cylinder exhaust port. Do not scratch cylinder or piston when cleaning exhaust port or allow carbon particles to enter cylinder.

- 4. Clean exhaust port (C).
- 5. Inspect heat shield (B) and replace if damaged.
- 6. Assemble heat shield (B).
- 7. Assemble muffler (A).
- 8. Tighten muffler mounting bolts (or nuts) to 90-110 kgf•cm (80-95 lbf•in).
- 9. Assemble muffler cover.



Carburetor Adjustment

Level 2

WARNING

Moving parts hazard. Contact with moving parts could cause bodily injury. Wear protective equipment. The cutting attachment may move during carburetor adjustment. Adjust the carburetor to assure blades do not move at idle or see your Authorized Service Dealer.

Engine Break-In

New engines must be operated a minimum duration of two tanks of fuel break-in before carburetor adjustments can be made. During break-in period your engine performance will increase and exhaust emissions will stabilize. Idle speed can be adjusted as required.

High Altitude Operation


This engine has been factory adjusted to maintain satisfactory starting and durability performance up to 330 m (1,100 ft.) above sea level (ASL). To maintain proper engine operation above 330 m (1,100 ft.) ASL the carburetor may need to be adjusted by an Authorized Service Dealer.

- For units equipped with a clutch, be sure the cutting attachment stops moving when the engine idles.
- Wear your protective equipment and observe all safety instructions.
- When the unit is turned off, make sure the cutting attachment has stopped before the unit is set down.

If the engine is adjusted for operation above 330 m (1,100 ft.) ASL, carburetor must be re-adjusted when operating engine below 330 m (1,100 ft.) ASL, otherwise severe engine damage may result.

Note: Every unit is run at the factory and carburetor is set in compliance with emission regulations. Carburetor adjustments, other than idle speed, must be performed by an Authorized Service Dealer.

1. Check idle speed and reset to 3,000 RPM (if required).Turn idle screw (A) clockwise to increase or counterclockwise to decrease idle speed.



Lubrication

Level 1.

Parts required: Lithium-based grease.


Gear Case


Note: Gear cases without a grease plug do not require lubrication.

- 1. Clean all loose debris from gear case.
- 2. Remove grease plug (A), if equipped, and check level of grease.
- 3. Add grease if necessary. Fill to bottom of grease plug hole.
- 4. Replace grease plug (A).
- 5. Connect spark plug lead to spark plug.


Drive Shaft (Flex Cable Only)

Loosen screw (B) and remove locating screw (C). Pull gear case and shield from drive shaft housing.






- 2. Pull flexible cable (D) from the drive shaft housing, wipe clean and coat with 15 ml (0.5 oz.) of grease.
- Slide flexible cable (D) back in 3. the drive housing. Do not get dirt on the flex cable.
- Assemble driveshaft to gear housing and shield assembly.



Nylon Line Head Disassembly Instructions

Note: For normal use, Speed-Feed® head disassembly is not necessary. However, if circumstances require disassembly, follow these instructions:

- Press top of locking tabs (A) on both sides of Speed-Feed® head to release cover (B) from knob (C).
- 2. Remove cover (B) from knob



Nylon Line Replacement

CAUTION


Wear gloves or personal injury may result:

- Cut-off knife is sharp.
- · Gear case and surrounding area may be hot.


WARNING

Never use wire or wire-rope that can break off and become a dangerous projectile. Serious injury can occur.


- Cut one piece of line to recommended length:
 - 2.4 mm (0.095 in.) diameter 6 m (20 ft.).
 - 2.0 mm (0.080 in.) diameter 6 m (20 ft.).



- 2. Align arrows on top of knob with openings in eyelets.
- 3. Insert one end of trimmer line into an evelet, and push line equal distance through trimmer head.




4. Hold trimmer head while turning knob clockwise to wind line onto spool until about 13 cm (5 in.) of each line remains exposed.



NOTICE

When the wear indicators located at the bottom of the Speed-Feed® head are worn smooth, or if holes appear, replacement of the cover or the entire Speed-Feed® head required.



Sharpening Metal Blades

WARNING

Metal blades are very sharp and can cause severe injuries, even if unit is off and blades are not moving. Avoid contact with blades. Wear gloves to protect hands.

Several styles of metal blades are approved for use on the brushcutter. The 8-tooth blade can be sharpened during normal maintenance. The clearing blade and 80-tooth blade require professional service.

Before sharpening, closely inspect blade for cracks (look at the bottom of each tooth and the center mounting hole closely), missing teeth and bending. If any of these problems are discovered, replace the blade.


When sharpening a blade, always remove the same amount of materials from each tooth to maintain balance. A blade that is not balanced will cause unsafe handling due to vibration and can result in blade failure




NOTICE

If an electric grinder is used, use care not to overheat teeth, do not allow tips/tooth to glow red or turn blue. Do not place blade in cooling water. This will change the temper of the blade and could result in blade failure.

File each tooth at a 30 degree angle a specific number of times, e.g., four strokes per tooth. Work your way around the blade until all teeth are sharp.



- Do not file the gullet (radius) of 2. the tooth with the flat file. The radius must remain. A sharp corner will lead to a crack and blade failure.
- 3. After sharpening teeth, check each tooth radius for evidence of a square (sharp) corner. Use the round (rat tail) file to renew the radius.



TROUBLESHOOTING

DANGER

Fuel vapors are flammable and can cause fire and/or explosion. Never test for ignition spark by grounding spark plug near cylinder plug hole, otherwise serious personal injury can result.

| E | NGINE PRO | BLEM TROU | BLESHOOTING | CHART |
|---|----------------------------------|------------------------------|---|---|
| Problem | Check | Status | Cause | Remedy |
| | Fuel at carbure- tor. | No fuel at carbure-tor. | Fuel filter or fuel line obstructed. | Clean or replace. See your Authorized Service Dealer. |
| | | No fuel at cylinder. | Carburetor | See your Authorized Service Dealer. |
| Engine starts hard. or Engine does not start. | Fuel at cylinder. | Muffler wet with fuel. | Fuel mixture too rich. | Open choke. Clean or replace air filter. Adjust carburetor. See your Authorized Service Dealer. |
| | Spark at end of plug wire. | No spark. | Stop switch OFF. Electrical problem. Interlock switch. | Turn switch to ON. See your Authorized Service Dealer. |

| Е | NGINE PRO | BLEM TROU | BLESHOOTING | CHART |
|---|-----------------------------|---|---|---|
| Problem | Check | Status | Cause | Remedy |
| Engine starts hard. or Engine does not start. | Spark at plug. | No spark. | Incorrect gap. Covered with carbon. Fouled with fuel. Spark plug defective. | Adjust to 0.65 mm (0.026 in.). Clean or replace spark plug. |
| | Air filter | Air filter dirty. | Normal wear. | Clean or replace. |
| | Fuel filter | Fuel filter dirty. | Contami- nants or residue in fuel. | Replace filter or replace fuel. |
| Engine runs, but | Fuel vent | Fuel vent plugged. | Contami- nated fuel. | Clean or replace. |
| dies. | Spark plug | Plug dirty or worn. | Normal wear. | Clean and adjust or replace. |
| Engine does not acceler- | Carbure- tor | Improper adjust- ment. | Vibration | Adjust |
| ate properly. | Cooling system | Cooling system dirty or plugged. | Extended operation in dirty or dusty locations. | Clean |
| | Spark arrester screen | Spark arrester screen plugged. | Normal wear. | Replace |
| Engine does not crank. | | N/A | Internal engine problem. | See your Authorized Ser- vice Dealer. |

STORAGE

SPECIFICATIONS

| MODEL | SRM-2620U |
|---------------------------------------|--|
| Length (without cutter head) | 1,786 mm (70.3 in.) |
| Width | 688 mm (27.0 in.) |
| Height | 512 mm (20.1 in.) |
| Weight - dry (without cutter head) | 5.6 kg (12.3 lb.) |
| Engine Type | Air-cooled, two-stroke, single cylinder gasoline engine |
| Bore | 34 mm (1.34 in.) |
| Stroke | 28 mm (1.10 in.) |
| Displacement | 25.4 cc (1.55 in. ³) |
| Exhaust | Spark arrester muffler or spark arrester muffler with catalyst |
| Carburetor | Diaphragm with purge pump |
| Ignition System | Flywheel magneto, capacitor discharge ignition type |
| Spark Plug | NGKCMR7H Gap 0.6 mm (0.026 in.) |
| Fuel | Mixed (gasoline and two-stroke oil) |
| Fuel/Oil Ratio | 50:1 |
| Gasoline | Use 89 Octane unleaded. Do not use fuel containing methyl alcohol, more than 10% ethyl alcohol or 15% MTBE. Do not use alternative fuels such as E15 or E85. |
| Oil | ISO-L-EGD (ISO/CD 13738) and J.A.S.O. M345- FD, two-stroke, air-cooled engine oil |
| Fuel Tank Capacity | 0.56 L (18.9 US fl. oz.) |
| Starter System | Automatic rewind starter |

| MODEL | SRM-2620U |
|-----------------------------|--|
| Clutch | Centrifugal type |
| Vibration Isolated | Rubber cushion on engine mount |
| System | Rubber anti-vibration grip on left handle |
| Operating Rod | 25.0 mm (1.0 in.) diameter aluminum tube |
| Drive Shaft | 6.15 mm (0.24 in.) flexible shaft |
| Gear Case Ratio | 1.62:1 |
| Rotating Direction | Counterclockwise (viewed from top) |
| Cutter Head | Speed-Feed [®] 400 LH nylon line head, line capacity 6.0 m (20 ft.) |
| Handle | U-handle |
| Shoulder Harness | Included |
| Idle Speed | 3,000 RPM |
| Clutch Engagement Speed | 4,100 RPM |
| Wide Open Throttle Speed | 10,500 RPM |

PRODUCT REGISTRATION

Thank you for choosing ECHO Power Equipment

Please go to http://www.echo-usa.com/Warranty/Register-Your-ECHO to register your new product on-line. It's FAST and EASY! NOTE: Your information will never be sold or misused by ECHO Incorporated. Registering your purchase enables us to contact you in the unlikely event of a service update or product recall, and verifies your ownership for warranty consideration.

If you do not have access to the Internet, you can complete the form below and mail to:

ECHO Incorporated, Product Registration, PO Box 1139, Lake Zurich, IL 60047.

PRODUCT REGISTRATION CARD : TARJETA DE REGISTRO : CARTE D'ENREGISTREMENT DU PRODUIT

lease Print : Por Favor Enscriba Con Letra De Molde : En Lettre Carré S.V.P.

ahorre una estampilia! Le alertaran sobre actualizaciones de producto y/o se le enviara información sobre los nuevos productos ECHO y las ofertas especiales. Simplemente visite: OPCIÓN POR INTERNET: ¡Registrese en la pagina web v www echo-usa com Confidential: Information provided will not be shared or sold

OPTION EN LIGNE: Enregistrer en ligne et épargner un timbre! Vous serez, informé sur les nouveaux produits ECHO et les mises à jour de produit ainsi que les offres spéciales. Simplement visitez le: www.echo-usa.com

☐ Rental Equip.

Primary use of tool: Professional Homeowner

| Purchaser's Name : Nombre del Comprador : Nom de l'acheteur | dor : Nom de l'ach | eteur | nimida vec or too: Uso primario de la herramienta: Drofesional Dueño de casa DAquiler Usoge principal : D Professionnel D Residential D Location |
|--|--|--|---|
| | | | Do you wish to receive periodic ECHO product information and special offers |
| Address : Dirección : Adresse | | | by é-mail? ☐ Yes ☐ No |
| | | | ¿Desea usted recibir información periódica y ofertas especiales por correo electronico sobre el producto ECHO? ☐ Yes ☐ No |
| | | | ormation sur les p |
| City : Ciudad : Ville | State : Estado : | Zip Code : Código Postal : Code Postal | ECHO et les offres spéciales par courrier électronique ? Oui Non |
| | Province | | Did you visit the ECHO website before purchasing your product? □ Yes □ No |
| E-Mail Address : Dirección De Correo Electrónico : Courrier Électronique | Electrónico : Courri | er Électronique | Visitó usted la pagina web ECHO antes de comprar su producto? ☐ si ☐ No |
| | | | Avez-vous visité le site d'ECHO avant de procurer votre produit? Oui □ Non |
| Phone Number : Número De Teléfono : Téléphone | | Date of Purchase : Fecha de la Compra : | What factor(s) most influenced your purchase? |
| | 7 | Date de l'achat | □ Performance □ Price □ Dealer □ Dealer □ Performance □ Price □ Dealer □ D |
| | | | |
| Where Purchased : Nombre del Almacén donde fue Comprado : Lieu d'achat | donde fue Compra | ado : Lieu d'achat | nfluenció más en su com |
| | | | nto 🗖 Precio |
| | | | Experiencia Anterior |
| | | | ☐ Amigo/Familia ☐ Marca ☐ Garantía |
| Model Number: Numero del Modelo: No | . de modéle Seria | Model Number : Numero del Modelo : No. de modéle Serial Number : Numero de Serie : No. de série | steurs |
| | | | ance Prix |
| | | | ☐ Experience |
| Registering your purchase enables us to contact you ownership in the event of loss. El registrar su com- | ou in the unlikely event | of a service update or product recall and verifies your | ☐ Ami/Famille ☐ Marque ☐ Garantie |
| como el aviso de tiempo de servicio o la revocació como el aviso de tiempo de servicio o la revocació L'enregistrement de votre achat nous permettra de d'antraign ou de capació di produit el vierifica que | n del producto y verific vous contacter dans le | connocidity in recoverable consequence in consequence and the propriet of the consequence | ECHO INC, 400 Oakwood Rd, Lake Zurich, IL 60047 1,800.432,ECHO WWW.ECHO-USA.COM |
| u entretten ou de lappet un produit et vermei que v | ous etes le proprietaire | ell das de voi ou de perte. | |

NOTES SRM-2620U

NOTES



U79612001001 - U79612999999 U87312001001 - U87312999999 U79713001001 - U79713999999 U87413001001 - U87413999999 U99015001001 - U99015999999



400 Oakwood Road Lake Zurich, IL 60047

www.echo-usa.com